ANNOUNCEMENT APPLIANCE

MODEL AA-4860

USER GUIDE

Introduction

The *Announcement Appliance* Model AA-4860 is a 'no-frills' automatic telephone voice announcer. Importance has been placed on good quality voice reproduction rather than supplementary facilities. Also, no external power supply is required.

You can personally record your voice announcement from any telephone and the announcement can run for up to two minutes (longer to order).

Applications for this device include recorded information services, automatic call distribution (ACD) announcements and Operator overflow answering.

Connection

The *Announcement Appliance* is simply connected to any two wire analogue (ring in/loop out) telephone line using the line cord provided. No external power is required for the system to operate.

When the Announcement Appliance is playing or recording, the 'Record/Play' LED indicator illuminates.

Instructions

To Record Your Announcement

- Dial up the Announcement Appliance and wait for it to answer.
- Press # during the current announcement so that it stops playing.
- Enter the preset four digit PIN (the default PIN is 1234).
- Listen for the 'beep' tone and then start dictating your new announcement into the telephone.
- To finish recording, press #. The new announcement will be replayed to you.

Specifications

Enclosure Injection molded ABS.
Dimensions 50 mm x 110 mm x 80 mm.

Operating Temperature Range -10 → +70 C. Voice Recording /Playback

Input Sample Rate
Upper pass band
Message retention
100 years

Message retention 100 years.Record Cycles 100, 000.

Messages length
 Output level
 Up to 120 seconds.
 -13.5 → 0 dBm adjustable.

• Frequency range 300 Hz → 3.4 kHz.

Line Interface Two wire analogue ring in, loop out. Connector RJ12.

Displays Record/Play LED indicator (green).

NZ Telepermit PTC 212/92/005.
ACA Supplier's Code Number N468.

Warranty Two years. specifications subject to change without notice

Proudly Designed and Manufactured in Australia



Telephone: +61 3 9758 5933